

## 2.07 PRIMAFLEX PVC L

Temperature range 0 °C bis 70 °C



### Description

Very lightweight, very flexible versatile PVC flex hose. Made of elastic PVC with concealed, coated spring steel spiral.

Very suitable for passing through gaseous media, vapours and dusts.

Available in our online shop

### Properties

- Highly elastic request
- Very lightweight
- Highly flexible
- High compressibility
- Non-kinking
- Smooth interior
- Wall thickness: 0.40 mm.

### Anwendungsbereiche

Ventilation, Ventilation, Dust removal, Suction technology, PVC hoses, Exhaust air systems, Suction hoses, dusts and powder, Suction hoses, air and gaseous media, Plant engineering, Roof ventilation, Drying screed, Air-conditioning and ventilation technology, Kitchen range hood, Ventilation technology, Dust suction

### Length

Standard length: 10m

### Further informations

Standard color: grey, but also available in black or transparent.

Special colors: other RAL colors upon

# TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Article-No.
40	35	0,35	0,15	0,202	10	6051040
50	38	0,35	0,145	0,254	10	6051050
60	49	0,3	0,12	0,305	10	6051060
70	53	0,3	0,1	0,356	10	6051070
75	56	0,3	0,09	0,382	10	6051075
80	63	0,25	0,09	0,406	10	6051080
100	70	0,2	0,08	0,55	10	6051100
125	85	0,1	0,06	0,69	10	6051125
150	100	0,08	0,05	0,8	10	6051150
175	123	0,06	0,04	0,965	10	6051175
200	158	0,05	0,03	1,078	10	6051200
250	175	0,04	0,03	1,348	10	6051250
300	210	0,03	0,02	1,62	10	6051300
350	245	0,02	0,02	1,889	10	6051350
400	280	0,02	0,02	2,16	10	6051400
450	315	0,01	0,01	2,43	10	6051450
500	350	0,01	0,01	2,699	10	6051500