

## 2.05 PRIMAFLEX PVC SUPER L

Temperature range 0 °C bis 70 °C



### Description

Very lightweight PVC flex hose made of elastic PVC with encased spring steel spiral on the inside. Ideally suited for the extraction of air, gasses and vapours.

Available in our online shop

### Properties

- Very flexible
- Very lightweight
- Highly elastic
- High compression capacity
- Largely smooth on the inside
- 0,30 - 0,36 mm Wall thickness

### Application ranges

Supply and exhaust ventilation, dedusting, suction technology, PVC hoses, exhaust air systems, suction hoses – dusts and powders, suction hoses – air and gaseous media, plant engineering, roof ventilation, elastic hoses – special, building drying, blower hose, ventilator hose, ventilation technology, dust extraction

### Length

Standard length: 10m

### Further informations

Standard color: black, but also available in grey or transparent.

Special colors: other RAL colors upon request.

# TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Outer-Ø (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Article-No.
25	31	25	1,7	0,2	0,27	10	2031025
28	34	28	1,6	0,2	0,28	10	2031028
32	38	32	1,5	0,2	0,35	10	2031032
35	41	35	1,4	0,2	0,38	10	2031035
38	44	38	1,4	0,2	0,41	10	2031038
41	47	41	1,4	0,18	0,42	10	2031041
44	50	44	1,3	0,16	0,45	10	2031044
51	57	51	1,3	0,15	0,48	10	2031051
63	69	63	1	0,14	0,52	10	2031063
70	76	70	0,9	0,12	0,7	10	2031070
76	82	76	0,8	0,1	0,73	10	2031076
80	86	80	0,7	0,09	0,78	10	2031080
89	95	89	0,7	0,09	0,84	10	2031089
102	108	102	0,6	0,08	0,95	10	2031102